NSN 4820-01-209-0276

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-209-0276

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.250 inches
Adjustable Pressure Range:
+101.0 to 140.0 pounds per square inch
Maximum Operating Pressure:
140.0 pounds per square inch single response
Outside Diameter:
4.500 inches all ends
Thickness:
0.438 inches all ends
First Connection Face To Centerline Distance:
3.750 inches
Bolt Hole Diameter:
0.562 inches all ends
Second Connection Face To Centerline Distance:
3.000 inches
Bolt Circle Diameter:
3.375 inches all ends
Flange Face Design:
Plain all ends
Material:
Nickel alloy seat
Material Specification:
Qq-n-281 federal specification single material response seat
Media For Which Designed:
Water-oil-gas single response

NSN 4820-01-209-0276

Safety Relief Valve - Page 2 of 2



Style Designator:	:
-------------------	---

C1a angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-b-16541 spec.