

View Online at <https://aerobasegroup.com/nsn/4820-01-210-6868>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

8 all ends

Maximum Operating Temp:

450.0 degrees fahrenheit 1st response

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Bonnet packing

Valve Size:

4.000 inches

Maximum Operating Pressure:

200.0 pounds per square inch 2nd response

Outside Diameter:

9.000 inches all ends

Face To Face Distance:

11.500 inches

Thickness:

0.938 inches all ends

Bolt Hole Diameter:

0.750 inches all ends

Bolt Circle Diameter:

7.500 inches all ends

Flange Face Design:

Plain all ends

Material:

Steel uns j03002 body

Material Specification:

Astmb-6 (b) assn standard single material response flow control device

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

Err-090

Supplementary Features:

This item has been reviewed for asbestos material. The current approved sources 12168 has indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0