

View Online at <https://aerobasegroup.com/nsn/4820-01-210-6868>

**Flow Control Device:**

Disk

**Bonnet Type:**

Outside screw-yoke

**Bonnet Attachment Method:**

Bolted

**Bolt Hole Quantity:**

8 all ends

**Maximum Operating Temp:**

450.0 degrees fahrenheit 1st response

**Valve Operation Method:**

Manual

**Flange Shape:**

Round with holes all ends

**Connection Type:**

Flange all ends

**Features Provided:**

Bonnet packing

**Valve Size:**

4.000 inches

**Maximum Operating Pressure:**

200.0 pounds per square inch 2nd response

**Outside Diameter:**

9.000 inches all ends

**Face To Face Distance:**

11.500 inches

**Thickness:**

0.938 inches all ends

**Bolt Hole Diameter:**

0.750 inches all ends

**Bolt Circle Diameter:**

7.500 inches all ends

**Flange Face Design:**

Plain all ends

**Material:**

Steel uns j03002 body

**Material Specification:**

Astmb-6 (b) assn standard single material response flow control device

**Media For Which Designed:**

Water-oil-gas 2nd response

**Style Designator:**

Err-090

**Supplementary Features:**

This item has been reviewed for asbestos material. The current approved sources 12168 has indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0