## NSN 4820-01-210-9599

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-210-9599

Pipe Size Accommodated:
0.750 inches 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 2nd end
Maximum Operating Temp:
180.0 degrees fahrenheit single response
Connection Style:
Socket with brazing ring 1st end
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 2nd end
Connection Type:
Unthreaded internal pipe 1st end
Adjustable Pressure Range:
+648.0 to 714.0 pounds per square inch
Maximum Operating Pressure:
1500.0 pounds per square inch single response
Outside Diameter:
3.812 inches 2nd end
Thickness:
0.438 inches 2nd end
Bolt Hole Diameter:
0.562 inches 2nd end
Bolt Circle Diameter:
2.688 inches 2nd end
Flange Face Design:
Plain 2nd end
Material:
Steel stem
Material Specification:
Qq-n-281 federal specification single material response seat
Media For Which Designed:
Oxygen, gaseous 2nd response

## NSN 4820-01-210-9599

Safety Relief Valve - Page 2 of 2



Style Designator:
C1 angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0