## NSN 4820-01-212-2012

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-212-2012

Flow Control Device:
Piston
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
1000.0 degrees fahrenheit 1st response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Position:
Horizontal
Valve Size:
1.500 inches
Maximum Operating Pressure:
1480.0 pounds per square inch 2nd response
Outside Diameter:
6.125 inches all ends
Face To Face Distance:
9.500 inches
Thickness:
0.875 inches all ends
Bolt Hole Diameter:
0.875 inches all ends
Bolt Circle Diameter:
4.500 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.250 inches all ends
Raised Face Diameter:
2.875 inches all ends
Special Features:
Piston check type; integral hard faced seat; conventional port; chrome trim
Material:
Steel uns k03504 body
Material Specification:
Astm a105 assn standard single material response body
Media For Which Designed:

Water-oil-gas 2nd response

## NSN 4820-01-212-2012

Check Valve - Page 2 of 2



Style	Desig	nator:

Straight through flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0