## NSN 4820-01-212-8261

Globe Valve - Page 1 of 2

Flow Control Device:

**Bonnet Type:** 

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-212-8261

| Inside screw                                 |
|--|
| Bonnet Attachment Method:                    |
| Bolted                                       |
| Bolt Hole Quantity:                          |
| 14 all ends                                  |
| Maximum Operating Temp:                      |
| 425.0 degrees fahrenheit single response     |
| Valve Operation Method:                      |
| Manual                                       |
| Flange Shape:                                |
| Round with holes all ends                    |
| Connection Type:                             |
| Flange all ends                              |
| Valve Size:                                  |
| 8.000 inches                                 |
| Maximum Operating Pressure:                  |
| 100.0 pounds per square inch single response |
| Outside Diameter:                            |
| 12.375 inches all ends                       |
| Face To Face Distance:                       |
| 21.562 inches                                |
| Thickness:                                   |
| 0.625 inches all ends                        |
| <b>Bolt Hole Diameter:</b>                   |
| 0.688 inches all ends                        |
| Bolt Circle Diameter:                        |
| 11.062 inches all ends                       |
| Flange Face Design:                          |
| Plain all ends                               |
| Material:                                    |
| Nickel alloy flow control device             |
| Media For Which Designed:                    |
| Water-oil-gas single response                |
| Style Designator:                            |
| A1a straight through flanged ends            |
| Shelf Life:                                  |
| N/a  |
| Unit Of Measure:                             |
|  |

## NSN 4820-01-212-8261

Globe Valve - Page 2 of 2



| em |  |  |  |
|----|--|--|--|
|    |  |  |  |
|    |  |  |  |

No

Fiig:

A046b0