## NSN 4820-01-213-0992

Safety Relief Valve - Page 1 of 2

Flow Control Device:

**Bonnet Attachment Method:** 

Bonnet Type: Inside spring

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-213-0992

Union
Bolt Hole Quantity:
8 1st end
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
3.000 inches
Adjustable Pressure Range:
+111.0 to 127.0 pounds per square inch
Outside Diameter:
9.000 inches 1st end
Thickness:
0.938 inches 1st end
First Connection Face To Centerline Distance:
6.437 inches
Bolt Hole Diameter:
0.750 inches all ends
Second Connection Face To Centerline Distance:
6.187 inches
Bolt Circle Diameter:
7.500 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.438 inches 2nd end
Raised Face Diameter:
6.375 inches 1st end
Material:
Stainless steel stem
Media For Which Designed:
Air single response
Style Designator:
C1a angle flanged ends

## NSN 4820-01-213-0992

Safety Relief Valve - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0