NSN 4820-01-213-1531

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Attachment Method:

Disk Loading Method:

Bonnet Type: Inside spring

Disk

Union



View Online at https://aerobasegroup.com/nsn/4820-01-213-1531

| Spring |
|------------------------------------------------|
| Bolt Hole Quantity: |
| 8 1st end |
| End Application: |
| Combat system support equipment |
| Valve Operation Method: |
| Automatic |
| Flange Shape: |
| Round with holes all ends |
| Connection Type: |
| Flange all ends |
| Valve Size: |
| 6.000 inches |
| Adjustable Pressure Range: |
| +16.0/+19.0 pounds per square inch |
| Outside Diameter: |
| 7.688 inches 1st end |
| Thickness: |
| 0.563 inches 2nd end |
| First Connection Face To Centerline Distance: |
| 7.000 inches |
| Bolt Hole Diameter: |
| 0.688 inches 2nd end |
| Second Connection Face To Centerline Distance: |
| 6.750 inches |
| Bolt Circle Diameter: |
| 8.875 inches 2nd end |
| Flange Face Design: |
| Plain all ends |
| Special Features: |
| Valve sz 4.000 in. By 6.000 in. |
| Material: |
| Steel comp 316 stem |
| Style Designator: |
| Err-090 |
| |
| |

NSN 4820-01-213-1531

Safety Relief Valve - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0