## NSN 4820-01-213-1531

Safety Relief Valve - Page 1 of 2

Flow Control Device:

**Bonnet Attachment Method:** 

**Disk Loading Method:** 

Bonnet Type: Inside spring

Disk

Union



View Online at https://aerobasegroup.com/nsn/4820-01-213-1531

Spring
Bolt Hole Quantity:
8 1st end
End Application:
Combat system support equipment
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
6.000 inches
Adjustable Pressure Range:
+16.0/+19.0 pounds per square inch
Outside Diameter:
7.688 inches 1st end
Thickness:
0.563 inches 2nd end
First Connection Face To Centerline Distance:
7.000 inches
Bolt Hole Diameter:
0.688 inches 2nd end
Second Connection Face To Centerline Distance:
6.750 inches
Bolt Circle Diameter:
8.875 inches 2nd end
Flange Face Design:
Plain all ends
Special Features:
Valve sz 4.000 in. By 6.000 in.
Material:
Steel comp 316 stem
Style Designator:
Err-090

## NSN 4820-01-213-1531

Safety Relief Valve - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0