NSN 4820-01-213-7962

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-213-7962

| Flow Control Device: | |
|--|--|
| Disk | |
| Bonnet Type: | |
| Inside spring | |
| Bonnet Attachment Method: | |
| Union | |
| Disk Loading Method: | |
| Spring | |
| Bolt Hole Quantity: | |
| 3 all ends | |
| Maximum Operating Temp: | |
| 425.0 degrees fahrenheit single response | |
| Valve Operation Method: | |
| Automatic | |
| Flange Shape: | |
| Round with holes all ends | |
| Connection Type: | |
| Flange all ends | |
| Valve Size: | |
| 0.500 inches | |
| Adjustable Pressure Range: | |
| +33.0/+50.0 pounds per square inch | |
| Maximum Operating Pressure: | |
| 100.0 pounds per square inch single response | |
| Outside Diameter: | |
| 3.562 inches all ends | |
| Thickness: | |
| 0.375 inches all ends | |
| First Connection Face To Centerline Distance: | |
| 2.375 inches | |
| Bolt Hole Diameter: | |
| 0.562 inches all ends | |
| Second Connection Face To Centerline Distance: | |
| 2.500 inches | |
| Bolt Circle Diameter: | |
| 2.437 inches all ends | |
| Flange Face Design: | |
| Plain all ends | |
| Material: | |
| Nickel alloy flow control device | |
| Media For Which Designed: | |

Fuel/oil, hydrocarbon single response

NSN 4820-01-213-7962

Safety Relief Valve - Page 2 of 2



| Style | Designator |
|--------|------------|
| Err-09 | 90 |

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0