

View Online at <https://aerobasegroup.com/nsn/4820-01-213-8414>

Flow Control Device:

Ball

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Union

Disk Loading Method:

Spring

Bolt Hole Quantity:

4 all ends

End Application:

Tarawa class lha

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

1.000 inches

Adjustable Pressure Range:

+65.0/+84.0 pounds per square inch

Outside Diameter:

4.250 inches 1st end

Thickness:

0.688 inches 2nd end

First Connection Face To Centerline Distance:

3.312 inches

Bolt Hole Diameter:

0.625 inches all ends

Second Connection Face To Centerline Distance:

3.250 inches

Bolt Circle Diameter:

3.125 inches 1st end

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.250 inches 2nd end

Raised Face Diameter:

2.000 inches 1st end

Special Features:

Valve sz 0.500 in. By 1.000 in.

Material:

Stainless steel stem

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0