N Sa



| NSN 4820-01-214-6896 Safety Relief Valve - Page 1 of 1 |
|--|
| View Online at https://aerobasegroup.com/nsn/4820-01-214-6896 |
| Thread Direction: |
| Right-hand all ends |
| Flow Control Device: |
| Diaphragm |
| Bonnet Type: |
| Inside screw |
| Bonnet Attachment Method: |
| Threaded |
| Maximum Operating Temp: |
| 175.0 degrees fahrenheit single response |
| Connection Style: |
| G9 plain, optional en (pipe) all ends |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Threaded internal pipe all ends |
| Adjustable Pressure Range: |
| +2.0 to 125.0 pounds per square inch |
| Maximum Operating Pressure: |
| 300.0 pounds per square inch single response |
| Thread Size: |
| 0.500 inches all ends |
| Material: |
| Aluminum body |
| Media For Which Designed: |
| Air single response |
| Style Designator: |
| C8 straight through note: to be used for valve bodies of one section only. |
| Thread Series Designator: |
| Npt all ends |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A046b0