NSN 4820-01-216-2234

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-216-2234

Thread Class:

3a all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Disk Loading Method:

Spring

Maximum Operating Temp:

275.0 degrees fahrenheit single response

Connection Style:

Flareless all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube all ends

Mounting Position:

Horizontal or vertical

Thready Qty Per Inch (tpi):

12 all ends

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

1.000 inches 1st end

Seat Angle:

12.0 degrees all ends

Material:

Steel comp 303 body

Material Specification:

Qq-s-764 federal specification single material response body

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Style Designator:

Straight thru

Thread Series Designator:

Unj all ends

Shelf Life:

N/a

Unit Of Measure:

NSN 4820-01-216-2234

Check Valve - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A530b0

Mil-std (military Standard):

Mil-s-5002 spec.