

View Online at <https://aerobasegroup.com/nsn/4820-01-216-4046>

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Union

Disk Loading Method:

Spring

Bolt Hole Quantity:

6 all ends

End Application:

Whiddey island class lsd

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

2.000 inches

Adjustable Pressure Range:

+57.0/+64.0 pounds per square inch

Outside Diameter:

5.562 inches 2nd end

Thickness:

0.500 inches 1st end

First Connection Face To Centerline Distance:

5.125 inches

Bolt Hole Diameter:

0.562 inches all ends

Second Connection Face To Centerline Distance:

4.250 inches

Bolt Circle Diameter:

5.000 inches 1st end

Flange Face Design:

Plain all ends

Material:

Nickel alloy stem

Style Designator:

Err-090

Furnished Items And Quantity:

1 lever

Specification Data:

81349-mil-v-24332 government specification

Specification Or Standard:

B grade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-v-24332 spec.