NSN 4820-01-216-4652

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-216-4652

Thread Class:	
---------------	--

2a all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

125.0 degrees fahrenheit single response

Connection Style:

G50 external seat for gasket seal (boss) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded external boss 1st end

Maximum Operating Pressure:

35.0 pounds per square inch single response

Thread Size:

0.438 inches all ends

Opening Pressure Setting:

20.0 pounds per square inch

Material:

Steel comp 303 body

Material Specification:

Astm a582 assn standard single material response or qq-s-763 federal specification single material response body

Media For Which Designed:

Nitrogen, gaseous 1st response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

C5 straight through w/baffle

Thread Series Designator:

Unf all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 4820-01-216-4652

Safety Relief Valve - Page 2 of 2

Fiig: A046b0

