NSN 4820-01-216-5266

Stop-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-216-5266

view etimile at thispes/radiobacogresspicontwich local of 210 occor
Flow Control Device:
Disk
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
10 all ends
Maximum Operating Temp:
425.0 degrees fahrenheit single response
Valve Operation Method:
Manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Position:
Horizontal
Valve Size:
5.000 inches
Maximum Operating Pressure:
100.0 pounds per square inch single response
Outside Diameter:
9.062 inches all ends
Face To Face Distance:
14.250 inches
Thickness:
0.562 inches all ends
Bolt Hole Diameter:
0.688 inches all ends
Bolt Circle Diameter:
7.812 inches all ends
Flange Face Design:
Plain all ends
Material:
Nickel alloy flow control device
Material Specification:
Qq-n-288, comp e federal specification single material response seat
Style Designator:
Straight through flanged ends
Shelf Life:
N/a

NSN 4820-01-216-5266

Stop-check Valve - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A530b0