## NSN 4820-01-217-5712

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-217-5712 Flow Control Device: Disk **Disk Loading Method:** Spring **Bolt Hole Quantity:** 6 2nd end **Valve Operation Method:** Automatic Flange Shape: Round with holes all ends **Connection Type:** Flange all ends Valve Size: 2.500 inches **Adjustable Pressure Range:** +558.0/+677.0 pounds per square inch **Outside Diameter:** 7.500 inches 1st end Thickness: 1.375 inches 1st end **First Connection Face To Centerline Distance:** 5.500 inches **Bolt Hole Diameter:** 0.812 inches 1st end **Second Connection Face To Centerline Distance:** 5.750 inches **Bolt Circle Diameter:** 5.875 inches 1st end Flange Face Design: Raised straight 2nd end **Raised Face Height:** 0.250 inches 1st end **Raised Face Diameter:** 5.000 inches 1st end Material: Stainless steel stem **Material Specification:** Qq-s-763, 416 federal specification single material response stem Style Designator:

Err-090 Shelf Life: N/a

## NSN 4820-01-217-5712

Safety Relief Valve - Page 2 of 2



Ullit Ol Weasule.	ι	Jnit	Of	Measure:
-------------------	---	------	----	----------

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-s-15083 spec.