NSN 4820-01-217-9827

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-217-9827

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Bolt Hole Quantity:
10 all ends
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
5.000 inches
Adjustable Pressure Range:
+51.0 to 57.0 pounds per square inch
Maximum Operating Pressure:
125.0 pounds per square inch single response
Outside Diameter:
9.062 inches all ends
Thickness:
0.562 inches all ends
First Connection Face To Centerline Distance:
6.500 inches
Bolt Hole Diameter:
0.688 inches all ends
Second Connection Face To Centerline Distance:
6.500 inches
Bolt Circle Diameter:
7.812 inches all ends
Flange Face Design:
Plain all ends
Material:
Copper alloy body
Material Specification:
Qq-b-637 federal specification single material response stem
Style Designator:
A7a angle flanged ends

NSN 4820-01-217-9827

Safety Relief Valve - Page 2 of 2



_				-		
C	h	0	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0