## NSN 4820-01-218-2502

Calibrated Flow Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-218-2502

| Body Material:  |
|---|
| Steel   |
| Body Style:   |
| Straight thru   |
| Media For Which Designed:   |
| Hydraulic oil   |
| First End Connection Type:  |
| Threaded internal pipe  |
| First End Style Designator:   |
| Optional end  |
| First End Thread Size And Series/type Designator:   |
| 3/4-14 nptf   |
| First End Thread Direction:   |
| Right-hand  |
| Second End Relationship With First End:   |
| Identical   |
| Flow Control Device:  |
| Needle  |
| End Connection Quantity:  |
| 2   |
| Valve Discharge Flow Rate:  |
| 2.5 gallons per minute and 25.0 gallons per minute  |
| Regulation Type:  |
| 1st stage manual, 2nd stage automatic   |
| Manual Control Method:  |
| Knob  |
| Maximum Inlet Pressure Rating:  |
| 3000.0 pounds per square inch   |
| Special Features:   |
| With viton seals; reverse check type, 35 gpm through check; adjustable flow; inline mounted |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A21100  |
|   |
|   |