

View Online at <https://aerobasegroup.com/nsn/4820-01-218-3303>

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Union

Disk Loading Method:

Spring

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

650.0 degrees fahrenheit 2nd response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

1.000 inches

Adjustable Pressure Range:

+47.0/+54.0 pounds per square inch

Maximum Operating Pressure:

185.0 pounds per square inch 2nd response

Outside Diameter:

6.000 inches 1st end

Thickness:

0.812 inches 1st end

First Connection Face To Centerline Distance:

4.750 inches

Bolt Hole Diameter:

0.750 inches 1st end

Second Connection Face To Centerline Distance:

4.937 inches

Bolt Circle Diameter:

4.750 inches 1st end

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.438 inches 2nd end

Raised Face Diameter:

3.625 inches 1st end

Material:

Stainless steel stem

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0