## NSN 4820-01-218-6620

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-218-6620

| Pipe Size Accommodated:                                      |
|--|
| 0.750 inches all ends  |
| Flow Control Device:   |
| Disk   |
| Bonnet Type:   |
| Inside screw   |
| Bonnet Attachment Method:                                    |
| Bolted   |
| Disk Loading Method:   |
| Spring   |
| Maximum Operating Temp:                                      |
| 250.0 degrees fahrenheit single response                     |
| Connection Style:  |
| Socket with brazing ring all ends                            |
| Valve Operation Method:                                      |
| Automatic  |
| Connection Type:   |
| Unthreaded internal pipe all ends                            |
| Adjustable Pressure Range:                                   |
| +225.0 to 275.0 pounds per square inch                       |
| Maximum Operating Pressure:                                  |
| 400.0 pounds per square inch single response                 |
| Material:  |
| Nickel alloy flow control device                             |
| Material Specification:                                      |
| Qq-n-281 federal specification single material response stem |
| Style Designator:  |
| C1 angle   |
| Furnished Items And Quantity:                                |
| 1 lever  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A046b0   |
|  |