NSN 4820-01-219-5593

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-219-5593 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: Disk **Maximum Operating Temp:** 250.0 degrees fahrenheit single response **Minimum Operating Temp:** -40.0 degrees fahrenheit **Connection Style:** G42 flared (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends Thready Qty Per Inch (tpi): 18 all ends **Maximum Operating Pressure:** 200.0 pounds per square inch single response **Thread Size:** 0.375 inches all ends Seat Angle: 37.0 degrees all ends **Opening Pressure Setting:** 35.0 pounds per square inch **Special Features:** Packing; general purpose-buna-n, per mil-p-25732. Material: Aluminum alloy body **Material Specification:** Qq-a-225/6 federal specification single material response body **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-8625 type 1 military specification single treatment response **Style Designator:** Err-090 **Thread Series Designator:** Unj all ends

N/a

Shelf Life:

NSN 4820-01-219-5593

Safety Relief Valve - Page 2 of 2



Demilitarization:	
No	
Fiig:	
A046b0	

Unit Of Measure:

Mil-std (military Standard):

spec.