NSN 4820-01-219-6518

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Attachment Method:

Disk Loading Method:

Bolt Hole Quantity:

Bonnet Type: Inside spring

Disk

Bolted

Spring



View Online at https://aerobasegroup.com/nsn/4820-01-219-6518

8 1st end
Maximum Operating Temp:
450.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
4.000 inches
Maximum Operating Pressure:
285.0 pounds per square inch single response
Outside Diameter:
9.000 inches 1st end
Thickness:
0.938 inches 1st end
First Connection Face To Centerline Distance:
6.375 inches
Bolt Hole Diameter:
0.625 inches all ends
Second Connection Face To Centerline Distance:
6.125 inches
Bolt Circle Diameter:
7.500 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Diameter:
6.188 inches 1st end
Material:
Stainless steel stem
Material Specification:
Astm a582 type 416 cond a assn standard single material response stem

NSN 4820-01-219-6518

Safety Relief Valve - Page 2 of 2



Sty				

C1a angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0