NSN 4820-01-219-6523

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-219-6523

Design of Towns
Bonnet Type: Inside screw
Bonnet Attachment Method:
Bolted
20.104
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
0.750 inches
Adjustable Pressure Range:
+163.0 to 201.0 pounds per square inch
Maximum Operating Pressure:
400.0 pounds per square inch single response
Outside Diameter:
4.250 inches 1st end
Thickness:
0.562 inches 1st end
First Connection Face To Centerline Distance:
3.672 inches
Bolt Hole Diameter:
0.625 inches all ends
Second Connection Face To Centerline Distance:
3.672 inches
Bolt Circle Diameter:
3.125 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
2.000 inches 1st end
Material:
Stainless steel stem

NSN 4820-01-219-6523

Safety Relief Valve - Page 2 of 2



Media For Which Designed:
Water-oil-gas single response
Style Designator:
C1a angle flanged ends
Furnished Items And Quantity:
1 lever
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0