## NSN 4820-01-220-5536

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Poppet

**Bonnet Type:** 



View Online at https://aerobasegroup.com/nsn/4820-01-220-5536

Inside screw
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
12 all ends
Maximum Operating Temp:
610.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
6.000 inches
Maximum Operating Pressure:
30.0 pounds per square inch single response
Opening Pressure Setting:
10.0 pounds per square inch
Outside Diameter:
10.125 inches all ends
Thickness:
0.562 inches all ends
First Connection Face To Centerline Distance:
8.000 inches
Bolt Hole Diameter:
0.688 inches all ends
Second Connection Face To Centerline Distance:
8.000 inches
Bolt Circle Diameter:
8.875 inches all ends
Flange Face Design:
Plain all ends
Material:
Steel uns j92650 flow control device
Style Designator:
C1a angle flanged ends
Shelf Life:
N/a

## NSN 4820-01-220-5536

Safety Relief Valve - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A046b0