NSN 4820-01-220-5758

Valve Locking Plate - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-220-5758

	_		
General	11000	rintion	•
General	DESC	HULIUH	

Nickel-copper alloy, qq-n-281, cl a, form 1; hex shape, 3.250 in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 1.770 min 1.780 maximum in. W across flats, 0.625 in. O/a h, 0.625 in	SS
inside flats; with six 0.281 in. Diameter holes, equally spaced on 2.500 in. Diameter bolt circle	

inside flats; with six 0.281 in. Diameter holes, equally spaced on 2.500 in. Diameter bolt circle
Shelf Life:
N/a

Unit Of Measure:

Demilitarization:

No