NSN 4820-01-220-6601

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Attachment Method:

Bonnet Type: Inside spring

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-220-6601

megrai
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
2.500 inches
Adjustable Pressure Range:
+72.0 to 86.0 pounds per square inch
Outside Diameter:
5.000 inches 2nd end
Thickness:
0.860 inches 2nd end
First Connection Face To Centerline Distance:
6.000 inches
Bolt Hole Diameter:
0.625 inches all ends
Second Connection Face To Centerline Distance:
4.875 inches
Bolt Circle Diameter:
5.500 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.060 inches all ends
Raised Face Diameter:
4.120 inches 1st end
Material:
Nickel alloy seat
Style Designator:
C1a angle flanged ends

NSN 4820-01-220-6601

Safety Relief Valve - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0