NSN 4820-01-220-7674



Safety Relief Valve - Page 1 of 2	Group
View Online at https://aerobasegroup.com/nsn/4820-01-220-7674	
Flow Control Device:	
Disk	
Bonnet Type:	
Outside screw-yoke	
Bonnet Attachment Method:	
Bolted	
Disk Loading Method:	
Spring	
Bolt Hole Quantity:	
8 all ends	
Valve Operation Method:	
Automatic	
Flange Shape:	
Round with holes all ends	
Connection Type:	
Flange all ends	
Valve Size:	
4.000 inches	
Adjustable Pressure Range:	
+144.0/+167.0 pounds per square inch	
Outside Diameter:	
9.000 inches 2nd end	
Thickness:	
1.000 inches 1st end	
First Connection Face To Centerline Distance:	
8.250 inches	
Bolt Hole Diameter:	
0.875 inches 1st end	
Second Connection Face To Centerline Distance:	
7.750 inches	
Bolt Circle Diameter:	
9.500 inches 1st end	
Flange Face Design:	
Raised straight all ends	

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

8.500 inches 1st end

Material:

Stainless steel stem

Media For Which Designed:

Steam single response

NSN 4820-01-220-7674

Safety Relief Valve - Page 2 of 2



Style	Designator:
Err-09	90

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No Fiig:

A046b0