NSN 4820-01-220-8278

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-220-8278 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 275.0 degrees fahrenheit single response **Connection Style:** G43 external seat for gasket seal (boss) 2nd end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 14 2nd end Adjustable Pressure Range: +160.0 to 240.0 pounds per square inch **Maximum Operating Pressure:** 2500.0 pounds per square inch single response **Thread Size:** 0.875 inches all ends Seat Angle: 37.0 degrees 2nd end **Opening Pressure Setting:** 200.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.625 inches 1st end Material: Stainless steel body Media For Which Designed: Helium 2nd response **Style Designator:** A1 straight thru **Thread Series Designator:** Unj 2nd end Shelf Life: N/a

Unit Of Measure:

NSN 4820-01-220-8278

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0