NSN 4820-01-221-1578

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Type:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-221-1578

Inside screw
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.500 inches
Adjustable Pressure Range:
+8.0/+10.0 pounds per square inch
Maximum Operating Pressure:
400.0 pounds per square inch single response
Outside Diameter:
5.000 inches 2nd end
Thickness:
0.938 inches 1st end
First Connection Face To Centerline Distance:
5.370 inches
Bolt Hole Diameter:
0.750 inches 1st end
Second Connection Face To Centerline Distance:
5.680 inches
Bolt Circle Diameter:
6.000 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
5.000 inches 1st end
Material:
Stainless steel seat

NSN 4820-01-221-1578

Safety Relief Valve - Page 2 of 2



Media For Which Designed:	
Water-oil-gas single response	
Style Designator:	
C1a angle flanged ends	
Furnished Items And Quantity:	
1 lever	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

Fiig: A046b0