## NSN 4820-01-221-1578

Safety Relief Valve - Page 1 of 2

**Flow Control Device:** 

Bonnet Type: Inside screw

Disk

View Online at https://aerobasegroup.com/nsn/4820-01-221-1578



## **Bonnet Attachment Method:** Bolted **Bolt Hole Quantity:** 4 all ends **Maximum Operating Temp:** 250.0 degrees fahrenheit single response Valve Operation Method: Automatic Flange Shape: Round with holes all ends **Connection Type:** Flange all ends Valve Size: 1.500 inches Adjustable Pressure Range: +8.0/+10.0 pounds per square inch Maximum Operating Pressure: 400.0 pounds per square inch single response **Outside Diameter:** 5.000 inches 2nd end Thickness: 0.938 inches 1st end **First Connection Face To Centerline Distance:** 5.370 inches **Bolt Hole Diameter:** 0.750 inches 1st end **Second Connection Face To Centerline Distance:** 5.680 inches **Bolt Circle Diameter:** 6.000 inches 1st end Flange Face Design: Raised straight all ends **Raised Face Height:** 0.062 inches all ends **Raised Face Diameter:** 5.000 inches 1st end

Material:

Stainless steel seat

## NSN 4820-01-221-1578

Safety Relief Valve - Page 2 of 2



Media For Which Designed:

Water-oil-gas single response

## Style Designator:

C1a angle flanged ends

Furnished Items And Quantity:

1 lever

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A046b0