

View Online at <https://aerobasegroup.com/nsn/4820-01-221-2049>

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Union

Disk Loading Method:

Spring

Bolt Hole Quantity:

6 all ends

Maximum Operating Temp:

650.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

2.500 inches

Adjustable Pressure Range:

+5.0 to 10.0 pounds per square inch

Maximum Operating Pressure:

200.0 pounds per square inch 1st response

Outside Diameter:

6.125 inches all ends

Thickness:

0.625 inches all ends

First Connection Face To Centerline Distance:

6.000 inches

Bolt Hole Diameter:

0.562 inches all ends

Second Connection Face To Centerline Distance:

5.000 inches

Bolt Circle Diameter:

5.000 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

4.000 inches all ends

Material:

Stainless steel stem

Media For Which Designed:

Air 1st response

Style Designator:

C1a angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0