## NSN 4820-01-221-5545

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-221-5545

Flow Control Device:					
Disk					
Bonnet Type:					
Inside screw					
Bonnet Attachment Method:					
Bolted					
Disk Loading Method:					
Spring					
Bolt Hole Quantity:					
4 all ends					
Maximum Operating Temp:					
250.0 degrees fahrenheit single response					
Valve Operation Method:					
Automatic or manual					
Flange Shape:					
Round with holes all ends					
Connection Type:					
Flange all ends					
Valve Size:					
1.500 inches					
Adjustable Pressure Range:					
+27.0/+33.0 pounds per square inch					
Maximum Operating Pressure:					
150.0 pounds per square inch single response					
Outside Diameter:					
5.000 inches 2nd end					
Thickness:					
0.875 inches 1st end					
Bolt Hole Diameter:					
0.750 inches 1st end					
Bolt Circle Diameter:					
5.500 inches 1st end					
Flange Face Design:					
Raised straight all ends					
Raised Face Height:					
0.062 inches all ends					
Raised Face Diameter:					
3.562 inches 1st end					
Material:					
Steel comp 316 stem					
Style Designator:					

Err-090

## NSN 4820-01-221-5545

Safety Relief Valve - Page 2 of 2



Furni	shed	Items	And	Quantity:
4 1				

1 lever

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0