
NSN 4820-01-221-5545

Safety Relief Valve - Page 1 of 2





Flow Control Device: Disk Bonnet Type: Inside screw Bonnet Attachment Method: Bolted Disk Loading Method: Spring

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

250.0 degrees fahrenheit single response

Valve Operation Method:

Automatic or manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

1.500 inches

Adjustable Pressure Range:

+27.0/+33.0 pounds per square inch

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

5.000 inches 2nd end

Thickness:

0.875 inches 1st end

Bolt Hole Diameter:

0.750 inches 1st end

Bolt Circle Diameter:

5.500 inches 1st end

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

3.562 inches 1st end

Material:

Steel comp 316 stem

Style Designator:

Err-090

NSN 4820-01-221-5545

Safety Relief Valve - Page 2 of 2



Furnished Items And Quantity:

1 lever

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0