Fluid Pressure Regulating Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-221-5599

Streight Hru Media For Which Designed: Air and steam First End Connection Type: Threaded internal pipe First End Style Designator: Plain First End Thread Size And Series/type Designator: 1/2-14 npt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk End Connection Quantity: 2 Outlet Pressure Range: +25.0 to 400.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximun Intel Pressure Rating: 20000 pounds per square inch Outlet Pressure Accuracy Rating: 200.000 pounds per square inch Outlet Pressure Accuracy Rating: 200.000 pounds per square inch Cutter Pressure Accuracy Rating: 200.000 pounds per square inch Cutter Pressure Accuracy Rating: 200.000 pounds per square inch Cutter Pressure Accuracy Rating: 200.000 pounds per square inch	Body Material:		
Body Style: Straight thru Media For Which Designed: Air and steam First End Connection Type: Threaded internal pipe First End Style Designator: Plain First End Thread Size And Series/type Designator: 1/2-14 npt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk End Connection Quantity: 2 Outlet Pressure Range: +25.0 to 400.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximun Inlet Pressure Rating: 00.00 pounds per square inch Filter: Not included Filter: Not included Shelf Life: N/a Dist Of Measure: Nation Spring Maximun Inlet Pressure Rating: Solo opounds per square inch Filter: Not included	-		
Straight thru Media For Which Designed: Air and steam First End Connection Type: Threaded internal pipe First End Style Designator: Plain First End Thread Size And Series/type Designator: Plain First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk End Connection Quantity: 2 Coute Pressure Range: 425.0 to 400.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximun Inlet Pressure Rating: 600.0 pounds per square inch Filter: Not included Filter: Not included Filter: Na			
Air and steam First End Connection Type: Threaded internal pipe First End Style Designator: Plain First End Thread Size And Series/type Designator: 1/2-14 npt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk End Connection Quantity: 2 Outlet Pressure Range: +25.0 to 400.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 600.0 pounds per square inch Filter: Not included Tempurature Rating: 75.0.0 degrees fahrenheit Shelf Life: Na Unit Of Measure: Na Pare Label Spring No Filter: Not included Tempurature Rating: No Filter: Na Dict of Measure: <td></td> <td></td> <td></td>			
Air and steam First End Connection Type: Threaded internal pipe First End Style Designator: Plain First End Thread Size And Series/type Designator: 1/2-14 npt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk End Connection Quantity: 2 Outlet Pressure Range: +25.0 to 400.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 600.0 pounds per square inch Outlet Pressure Accuracy Rating: 200.000 pounds per square inch Filter: Not included Tempurature Rating: 750.0 degrees fahrenheit Shelf Life: Na Unit Of Measure: - Templitarization: No Filig:	-	Designed	
First End Connection Type: Threaded internal pipe First End Style Designator: Plain First End Thread Size And Series/type Designator: 1/2-14 pt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk End Connection Quantity: 2 Outlet Pressure Range: +25.0 to 400.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 600.0 pounds per square inch Filter: Not included Tempurature Rating: 750.0 degrees fahrenheit Sheff Life: N/a Unit Of Measure: - Permiltarization: No Filig:			
Threaded internal pipe First End Style Designator: Plain First End Thread Size And Series/type Designator: 1/2-14 npt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk End Connection Quantity: 2 Outlet Pressure Range: +25.0 to 400.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Intel Pressure Rating: 20.000 pounds per square inch Filter: Not included Filte: Na Conderges fahrenheit Sheff Life: Na Condenges fahrenheit Condenges fahren		ction Type	
First End Style Designator:PlainFirst End Thread Size And Series/type Designator:1/2-14 nptFirst End Thread Direction:Right-handSecond End Relationship With First End:IdenticalFlow Control Device:DiskEnd Connection Quantity:2Outlet Pressure Range:+25.0 to 400.0 pounds per square inchRegulation Type:Automatic single stageValve Loading Method:SpringMaximum Inlet Pressure Rating:600.0 pounds per square inchFilter:Not includedTempurature Rating:750.0 degrees fahrenheitShelf Life:NicNicPingNotion ComputeFilter:NaDistore Rating:750.0 degrees fahrenheitShelf Life:NaFilte:NaFilte:NaFilte:NaFilte:NaFilte:NaFilte:NaFilte:NaFilte:NaFilte:NaFilte:NaFilte:NaFilte:NaFilte:Filte:Filte:Filte:Filte:Filte:Filte:Filte:Filte:Filte:Filte:Filte:Filte: <tr< td=""><td></td><td></td><td></td></tr<>			
PlainFirst End Thread Size And Series/type Designator:1/2-14 nptFirst End Thread Direction:Right-handSecond End Relationship With First End:IdenticalFlow Control Device:DiskEnd Connection Quantity:2Outlet Pressure Range:+25.0 to 400.0 pounds per square inchRegulation Type:Automatic single stageValve Loading Method:SpringMaximum Inlet Pressure Rating:600.0 pounds per square inchFilter:Not includedTempurature Rating:50.0 degrees fahrenheitShelf Life:NaMain Contextion:SpringMattinum Inter Pressure Rating:60.0 pounds per square inchFilter:Not includedTempurature Rating:75.0.0 degrees fahrenheitShelf Life:NaFilte:NaFilte:NaFilte:NaFilte:NaFilte:NaFilte:NaFilte:NaFilte:NaFilte:NaFilte:NaFilte:NaFilte:Filte:Filte:Filte:Filte:Filte:Filte:Filte:Filte:Filte:Filte:Filte:Filte: <t< td=""><td></td><td></td><td></td></t<>			
First End Thread Size And Series/type Designator: 1/2-14 npt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk End Connection Quantity: 2 Outlet Pressure Range: +25.0 to 400.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 600.0 pounds per square inch Outlet Pressure Accuracy Rating: 20.0000 pounds per square inch Filter: Not included Tempurature Rating: 750.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:			
1/2-14 npt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk End Connection Quantity: 2 Outlet Pressure Range: +25.0 to 400.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 600.0 pounds per square inch Filter: Not included Tempurature Rating: 750.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:		Size And Series/type Designator:	
First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk End Connection Quantity: 2 Outlet Pressure Range: +25.0 to 400.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 600.0 pounds per square inch Outlet Pressure Accuracy Rating: 200.000 pounds per square inch Filter: Not included Tempurature Rating: 75.0.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure: - - Demilitarization: No Filg:		loize And Genesitype Designator.	
Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk End Connection Quantity: 2 Outlet Pressure Range: +25.0 to 400.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 600.0 pounds per square inch Outlet Pressure Accuracy Rating: 200.000 pounds per square inch Filter: Not included Tempurature Rating: 750.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure: - Demilitarization: No Filig:		Direction	
Second End Relationship With First End: Identical Flow Control Device: Disk End Connection Quantity: 2 Outlet Pressure Range: +25.0 to 400.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 600.0 pounds per square inch Outlet Pressure Accuracy Rating: 200.000 pounds per square inch Filter: Not included Tempurature Rating: 750.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure: - Demilitarization: No			
Identical Flow Control Device: Disk End Connection Quantity: 2 Cutlet Pressure Range: +25.0 to 400.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 600.0 pounds per square inch Outlet Pressure Accuracy Rating: 200.000 pounds per square inch Filter: Not included Filter: Not included Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	-	ationship With First End-	
Flow Control Device: Disk End Connection Quantity: 2 Outlet Pressure Range: +25.0 to 400.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 600.0 pounds per square inch Outlet Pressure Accuracy Rating: 200.000 pounds per square inch Filter: Not included Fempurature Rating: 750.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure: Demilitarization: No			
Disk End Connection Quantity: 2 Outlet Pressure Range: +25.0 to 400.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 600.0 pounds per square inch Outlet Pressure Accuracy Rating: 200.000 pounds per square inch Filter: Not included Tempurature Rating: 750.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:		vice	
End Connection Quantity: 2 Outlet Pressure Range: +25.0 to 400.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 600.0 pounds per square inch Outlet Pressure Accuracy Rating: 200.000 pounds per square inch Filter: Not included Tempurature Rating: 750.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:		vice.	
2 Outlet Pressure Range: +25.0 to 400.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 600.0 pounds per square inch Outlet Pressure Accuracy Rating: 200.000 pounds per square inch Outlet Pressure Accuracy Rating: 200.000 pounds per square inch Filter: Not included Tempurature Rating: 750.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure: Demilitarization: No		Quantity	
Outlet Pressure Range:+25.0 to 400.0 pounds per square inchRegulation Type:Automatic single stageValve Loading Method:SpringMaximum Inlet Pressure Rating:600.0 pounds per square inchOutlet Pressure Accuracy Rating:200.000 pounds per square inchFilter:Not includedTempurature Rating:750.0 degrees fahrenheitShelf Life:N/aInit Of Measure:Penilitarization:NoFilg:		Quantity.	
+25.0 to 400.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 600.0 pounds per square inch Outlet Pressure Accuracy Rating: 200.000 pounds per square inch Filter: Not included Tempurature Rating: 750.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure: Demilitarization: No		Range.	
Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 600.0 pounds per square inch Outlet Pressure Accuracy Rating: 200.000 pounds per square inch Filter: Not included Tempurature Rating: 750.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure: - No Filg:			
Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 600.0 pounds per square inch Outlet Pressure Accuracy Rating: 200.000 pounds per square inch Filter: Not included Tempurature Rating: 750.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure: Importation: No Filg:	-		
Valve Loading Method: Spring Maximum Inlet Pressure Rating: 600.0 pounds per square inch Outlet Pressure Accuracy Rating: 200.000 pounds per square inch Filter: Not included Tempurature Rating: 750.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure: Demilitarization: No			
Spring Maximum Inlet Pressure Rating: 600.0 pounds per square inch Outlet Pressure Accuracy Rating: 200.000 pounds per square inch Filter: Not included Filter: Not included Tempurature Rating: 750.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:			
Maximum Inlet Pressure Rating: 600.0 pounds per square inch Outlet Pressure Accuracy Rating: 200.000 pounds per square inch Filter: Not included Tempurature Rating: 750.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure: Demilitarization: No	-		
600.0 pounds per square inch Outlet Pressure Accuracy Rating: 200.000 pounds per square inch Filter: Not included Tempurature Rating: 750.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure: Demilitarization: No		Pressure Rating	
Outlet Pressure Accuracy Rating: 200.000 pounds per square inch Filter: Not included Tempurature Rating: 750.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure: Demilitarization: No		-	
200.000 pounds per square inch Filter: Not included Tempurature Rating: 750.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:		-	
Filter: Not included Tempurature Rating: 750.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure: Demilitarization: No			
Not included Tempurature Rating: 750.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:			
Tempurature Rating: 750.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:			
750.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:		ting:	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:			
N/a Unit Of Measure: Demilitarization: No Fiig:	-		
Unit Of Measure: Demilitarization: No Fiig:			
 Demilitarization: No Fiig:		-	
No Fiig:			
No Fiig:			
Fiig:			
-			
	A21100		