Fluid Pressure Regulating Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-221-6993

Body Material:
Aluminum alloy
Body Style:
Angle
Media For Which Designed:
Air
First End Connection Type:
Threaded internal boss
First End Style Designator:
Gasket seal
First End Thread Size And Series/type Designator:
9/16-18 npt
First End Thread Class:
3b
First End Thread Direction:
Right-hand
Second End Relationship With First End:
Identical
Flow Control Device:
Disk
End Connection Quantity:
2
2 Regulation Type:
Regulation Type:
Regulation Type: Automatic single stage
Regulation Type: Automatic single stage Valve Loading Method:
Regulation Type: Automatic single stage Valve Loading Method: Spring
Regulation Type: Automatic single stage Valve Loading Method: Spring Remote Actuation Method:
Regulation Type:Automatic single stageValve Loading Method:SpringRemote Actuation Method:Diaphragm
Regulation Type:Automatic single stageValve Loading Method:SpringRemote Actuation Method:DiaphragmMaximum Inlet Pressure Rating:
Regulation Type:Automatic single stageValve Loading Method:SpringRemote Actuation Method:DiaphragmMaximum Inlet Pressure Rating:300.0 pounds per square inch
Regulation Type:Automatic single stageValve Loading Method:SpringRemote Actuation Method:DiaphragmMaximum Inlet Pressure Rating:300.0 pounds per square inchOutlet Pressure Setting:
Regulation Type:Automatic single stageValve Loading Method:SpringRemote Actuation Method:DiaphragmMaximum Inlet Pressure Rating:300.0 pounds per square inchOutlet Pressure Setting:12.0 pounds per square inch
Regulation Type:Automatic single stageValve Loading Method:SpringRemote Actuation Method:DiaphragmMaximum Inlet Pressure Rating:300.0 pounds per square inchOutlet Pressure Setting:12.0 pounds per square inchFilter:
Regulation Type:Automatic single stageValve Loading Method:SpringRemote Actuation Method:DiaphragmMaximum Inlet Pressure Rating:300.0 pounds per square inchOutlet Pressure Setting:12.0 pounds per square inchFilter:Not included
Regulation Type:Automatic single stageValve Loading Method:SpringRemote Actuation Method:DiaphragmMaximum Inlet Pressure Rating:300.0 pounds per square inchOutlet Pressure Setting:12.0 pounds per square inchFilter:Not includedTempurature Rating:
Regulation Type:Automatic single stageValve Loading Method:SpringRemote Actuation Method:DiaphragmMaximum Inlet Pressure Rating:300.0 pounds per square inchOutlet Pressure Setting:12.0 pounds per square inchFilter:Not includedTempurature Rating:165.0 degrees fahrenheit
Regulation Type:Automatic single stageValve Loading Method:SpringRemote Actuation Method:DiaphragmMaximum Inlet Pressure Rating:300.0 pounds per square inchOutlet Pressure Setting:12.0 pounds per square inchFilter:Not includedTempurature Rating:165.0 degrees fahrenheitShelf Life:
Regulation Type:Automatic single stageValve Loading Method:SpringRemote Actuation Method:DiaphragmMaximum Inlet Pressure Rating:300.0 pounds per square inchOutlet Pressure Setting:12.0 pounds per square inchFilter:Not includedTempurature Rating:165.0 degrees fahrenheitShelf Life:N/a

No

NSN 4820-01-221-6993

Fluid Pressure Regulating Valve - Page 2 of 2

Fiig: A21100

