NSN 4820-01-221-8855

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Type:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-221-8855

Inside screw
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
100.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.000 inches
Adjustable Pressure Range:
+89.0/+110.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
4.250 inches all ends
Thickness:
0.562 inches all ends
First Connection Face To Centerline Distance:
3.594 inches
Bolt Hole Diameter:
0.625 inches all ends
Second Connection Face To Centerline Distance:
3.344 inches
Bolt Circle Diameter:
3.125 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
2.000 inches all ends
Material:
Stainless steel stem

NSN 4820-01-221-8855

Safety Relief Valve - Page 2 of 2



Media For Which Designe	Which Designe	ed
-------------------------	---------------	----

Water-oil-gas single response

Style Designator:

C1a angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A046b0