

View Online at <https://aerobasegroup.com/nsn/4820-01-222-4417>

Overall Diameter:

6.625 inches

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

8

Valve Operation Method:

Manual

Connection Type:

Flange, round w/holes

Features Provided:

Bonnet packing

Maximum Operating Pressure And Media For Which Designed:

100.0 pounds per square inch water-oil-gas and 100.0 pounds per square inch water, salt

Stem Type:

Rising

Criticality Code Justification:

Zzzy

Maximum Operating Temperature And Media For Which Designed:

150.0 degrees fahrenheit water-oil-gas and 150.0 degrees fahrenheit water, salt

Flange Face Design:

Plain

Special Features:

Jflow control device: disk; renewable seat ring type: threaded; thickness: 0.500 in.; bolt hole diameter: 0.562 in.; bolt circle diameter: 5.500 in.; style: straight through flanged ends

Material:

Nickel alloy disk

Reference Number Differentiating Characteristics:

Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A500a0