NSN 4820-01-222-7499

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-222-7499

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
650.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.250 inches
Adjustable Pressure Range:
+5.0 to 10.0 pounds per square inch
Maximum Operating Pressure:
200.0 pounds per square inch 3rd response
Outside Diameter:
4.500 inches all ends
Thickness:
0.437 inches all ends
First Connection Face To Centerline Distance:
5.000 inches
Bolt Hole Diameter:
0.562 inches all ends
Second Connection Face To Centerline Distance:
4.250 inches
Bolt Circle Diameter:
3.375 inches all ends
Flange Face Design:
Plain all ends
Material:
Stainless steel stem
Media For Which Designed:

Air 1st response

NSN 4820-01-222-7499

Safety Relief Valve - Page 2 of 2



Style Designator:	Style	Des	igna	ıtor:
-------------------	-------	-----	------	-------

C1a angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0