NSN 4820-01-222-7812

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-222-7812 **Thread Class:** 3b 2nd end **Thread Direction:** Right-hand all ends Flow Control Device: Disk **Maximum Operating Temp:** 250.0 degrees fahrenheit single response **Connection Style:** Plain (tube) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal tube 2nd end Thready Qty Per Inch (tpi): 18 all ends **Thread Size:** 0.438 inches all ends **Opening Pressure Setting:** 14.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.250 inches 2nd end Material: Aluminum alloy 2024 body **Material Specification:** Qq-a-25/6 federal specification single material response body Media For Which Designed: Air 1st response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Style Designator:** Straight through note: to be used for valve bodies of one section only. **Thread Series Designator:** Uns all ends Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 4820-01-222-7812

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.