## NSN 4820-01-224-2104

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-224-2104

Flow Control Device:
Poppet
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
175.0 degrees fahrenheit single response
Width:
2.050 inches all ends
Length:
2.640 inches all ends
Valve Operation Method:
Automatic
Flange Shape:
Rectangular with holes all ends
Connection Type:
Flange all ends
Mounting Position:
Horizontal or vertical
Valve Size:
0.750 inches
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Face To Face Distance:
1.000 inches
Thickness:
1.000 inches all ends
Bolt Hole Diameter:
0.410 inches all ends
Center To Center Distance Between Bolt Holes Along Length:
1.875 inches all ends
Center To Center Distance Between Bolt Holes Along Width:
0.875 inches all ends
Flange Face Design:
Plain all ends
Material:
Steel flow control device
Material Specification:
Mil-p-25732 military specification single material response packing
Media For Which Designed:

Hydraulic fluid, petroleum base single response

## NSN 4820-01-224-2104

Check Valve - Page 2 of 2



Straight through flanged ends

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-p-25732 spec.