NSN 4820-01-224-2104

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-224-2104

| Flow Control Device: |
|---|
| Poppet |
| Disk Loading Method: |
| Spring |
| Bolt Hole Quantity: |
| 4 all ends |
| Maximum Operating Temp: |
| 175.0 degrees fahrenheit single response |
| Width: |
| 2.050 inches all ends |
| Length: |
| 2.640 inches all ends |
| Valve Operation Method: |
| Automatic |
| Flange Shape: |
| Rectangular with holes all ends |
| Connection Type: |
| Flange all ends |
| Mounting Position: |
| Horizontal or vertical |
| Valve Size: |
| 0.750 inches |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch single response |
| Face To Face Distance: |
| 1.000 inches |
| Thickness: |
| 1.000 inches all ends |
| Bolt Hole Diameter: |
| 0.410 inches all ends |
| Center To Center Distance Between Bolt Holes Along Length: |
| 1.875 inches all ends |
| Center To Center Distance Between Bolt Holes Along Width: |
| 0.875 inches all ends |
| Flange Face Design: |
| Plain all ends |
| Material: |
| Steel flow control device |
| Material Specification: |
| Mil-p-25732 military specification single material response packing |
| Media For Which Designed: |
| |

Hydraulic fluid, petroleum base single response

NSN 4820-01-224-2104

Check Valve - Page 2 of 2



Straight through flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-p-25732 spec.