## NSN 4820-01-226-2005

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-226-2005

Pipe Size Accommodated:
0.750 inches 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 2nd end
Maximum Operating Temp:
425.0 degrees fahrenheit single response
Connection Style:
Socket 1st end
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 2nd end
Connection Type:
Unthreaded internal pipe 1st end
Adjustable Pressure Range:
+0.0 to 15.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
3.875 inches 2nd end
Thickness:
0.344 inches 2nd end
Bolt Hole Diameter:
0.625 inches 2nd end
Bolt Circle Diameter:
2.750 inches 2nd end
Flange Face Design:
Plain 2nd end
Material:
Steel comp 1008 stem
Media For Which Designed:
Gas, inert 2nd response
Style Designator:
C1 angle

## NSN 4820-01-226-2005

Safety Relief Valve - Page 2 of 2



Furnished Items And Quantity:
1 lever
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A046b0