# NSN 4820-01-226-2005

Safety Relief Valve - Page 1 of 2





Pipe Size Accommodated:

0.750 inches 1st end

**Flow Control Device:** 

Disk

# Bonnet Type:

Inside screw

# **Bonnet Attachment Method:**

Threaded

# **Disk Loading Method:**

Spring

# **Bolt Hole Quantity:**

4 2nd end

#### **Maximum Operating Temp:**

425.0 degrees fahrenheit single response

#### **Connection Style:**

Socket 1st end

#### Valve Operation Method:

Automatic

# Flange Shape:

Round with holes 2nd end

# **Connection Type:**

Unthreaded internal pipe 1st end

# Adjustable Pressure Range:

+0.0 to 15.0 pounds per square inch

# Maximum Operating Pressure:

150.0 pounds per square inch single response

#### **Outside Diameter:**

3.875 inches 2nd end

#### Thickness:

0.344 inches 2nd end

#### **Bolt Hole Diameter:**

0.625 inches 2nd end

#### Bolt Circle Diameter:

2.750 inches 2nd end

#### Flange Face Design:

Plain 2nd end

# Material:

Steel comp 1008 stem

# Media For Which Designed:

Gas, inert 2nd response

#### Style Designator:

C1 angle

# NSN 4820-01-226-2005

Safety Relief Valve - Page 2 of 2



Furnished Items And Quantity:

1 lever

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A046b0