## NSN 4820-01-226-3246

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-226-3246

Bonnet Type:					
Inside spring					
Bonnet Attachment Method:					
Union					
Disk Loading Method:					
Spring					
Bolt Hole Quantity:					
4 all ends					
Valve Operation Method:					
Automatic					
Flange Shape:					
Round with holes all ends					
Connection Type:					
Flange all ends					
Valve Size:					
1.000 inches					
Adjustable Pressure Range:					
+30.0/+45.0 pounds per square inch					
Maximum Operating Pressure:					
150.0 pounds per square inch single response					
Outside Diameter:					
4.250 inches 1st end					
Thickness:					
0.438 inches all ends					
First Connection Face To Centerline Distance:					
3.250 inches					
Bolt Hole Diameter:					
0.625 inches all ends					
Second Connection Face To Centerline Distance:					
3.312 inches					
Bolt Circle Diameter:					
3.125 inches 1st end					
Flange Face Design:					
Raised straight all ends					
Raised Face Height:					
0.062 inches all ends					
Raised Face Diameter:					
2.000 inches 1st end					
Material:					
Stainless steel stem					

## NSN 4820-01-226-3246

Safety Relief Valve - Page 2 of 2



M	edia	For	Which	n Desid	med:
IV!	cuia	1 01	VVIIICI	I DESIG	HICU.

Steam single response

Style Designator:

Err-090

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0