

View Online at <https://aerobasegroup.com/nsn/4820-01-227-1013>

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Bolt Hole Quantity:

8 all ends

Maximum Operating Temp:

150.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

4.000 inches

Adjustable Pressure Range:

+56.0/+70.0 pounds per square inch

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

7.688 inches all ends

Thickness:

1.000 inches 1st end

First Connection Face To Centerline Distance:

5.375 inches

Bolt Hole Diameter:

0.562 inches all ends

Second Connection Face To Centerline Distance:

6.000 inches

Bolt Circle Diameter:

6.562 inches all ends

Flange Face Design:

Plain all ends

Material:

Nickel alloy flow control device

Style Designator:

Err-090

Supplementary Features:

This item has been reviewed for asbestos material. The current approved source, 15187, has indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0