NSN 4820-01-227-1897

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-227-1897

Bonnet Type:
Inside screw
Bonnet Attachment Method:
Threaded
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.000 inches
Adjustable Pressure Range:
+59.0 to 72.0 pounds per square inch
Maximum Operating Pressure:
400.0 pounds per square inch single response
Outside Diameter:
4.250 inches all ends
Thickness:
0.500 inches all ends
First Connection Face To Centerline Distance:
4.500 inches
Bolt Hole Diameter:
0.625 inches all ends
Second Connection Face To Centerline Distance:
4.125 inches
Bolt Circle Diameter:
3.125 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
2.000 inches all ends
Material:
Steel uns j03002 body

NSN 4820-01-227-1897

Safety Relief Valve - Page 2 of 2



Material Specification:
Astm b-61 assn standard single material response body
Media For Which Designed:
Water-oil-gas single response
Style Designator:
C1a angle flanged ends
Furnished Items And Quantity:
1 lever
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A046b0