NSN 4820-01-228-4260

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-228-4260

Inside spring
Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.000 inches
Adjustable Pressure Range:
+158.0 to 185.0 pounds per square inch
Maximum Operating Pressure:
286.0 pounds per square inch single response
Outside Diameter:
• • • • • • • • • • • • • • • • • • • •
6.000 inches 2nd end
6.000 inches 2nd end Thickness:
Thickness:
Thickness: 0.938 inches all ends
Thickness: 0.938 inches all ends First Connection Face To Centerline Distance:
Thickness: 0.938 inches all ends First Connection Face To Centerline Distance: 4.688 inches
Thickness: 0.938 inches all ends First Connection Face To Centerline Distance: 4.688 inches Bolt Hole Diameter:
Thickness: 0.938 inches all ends First Connection Face To Centerline Distance: 4.688 inches Bolt Hole Diameter: 0.750 inches 2nd end
Thickness: 0.938 inches all ends First Connection Face To Centerline Distance: 4.688 inches Bolt Hole Diameter: 0.750 inches 2nd end Second Connection Face To Centerline Distance:
Thickness: 0.938 inches all ends First Connection Face To Centerline Distance: 4.688 inches Bolt Hole Diameter: 0.750 inches 2nd end Second Connection Face To Centerline Distance: 4.875 inches
Thickness: 0.938 inches all ends First Connection Face To Centerline Distance: 4.688 inches Bolt Hole Diameter: 0.750 inches 2nd end Second Connection Face To Centerline Distance: 4.875 inches Bolt Circle Diameter:
Thickness: 0.938 inches all ends First Connection Face To Centerline Distance: 4.688 inches Bolt Hole Diameter: 0.750 inches 2nd end Second Connection Face To Centerline Distance: 4.875 inches Bolt Circle Diameter: 4.750 inches 2nd end
Thickness: 0.938 inches all ends First Connection Face To Centerline Distance: 4.688 inches Bolt Hole Diameter: 0.750 inches 2nd end Second Connection Face To Centerline Distance: 4.875 inches Bolt Circle Diameter: 4.750 inches 2nd end Flange Face Design:
Thickness: 0.938 inches all ends First Connection Face To Centerline Distance: 4.688 inches Bolt Hole Diameter: 0.750 inches 2nd end Second Connection Face To Centerline Distance: 4.875 inches Bolt Circle Diameter: 4.750 inches 2nd end Flange Face Design: Raised straight all ends
Thickness: 0.938 inches all ends First Connection Face To Centerline Distance: 4.688 inches Bolt Hole Diameter: 0.750 inches 2nd end Second Connection Face To Centerline Distance: 4.875 inches Bolt Circle Diameter: 4.750 inches 2nd end Flange Face Design: Raised straight all ends Raised Face Height:
Thickness: 0.938 inches all ends First Connection Face To Centerline Distance: 4.688 inches Bolt Hole Diameter: 0.750 inches 2nd end Second Connection Face To Centerline Distance: 4.875 inches Bolt Circle Diameter: 4.750 inches 2nd end Flange Face Design: Raised straight all ends Raised Face Height: 0.438 inches 1st end
Thickness: 0.938 inches all ends First Connection Face To Centerline Distance: 4.688 inches Bolt Hole Diameter: 0.750 inches 2nd end Second Connection Face To Centerline Distance: 4.875 inches Bolt Circle Diameter: 4.750 inches 2nd end Flange Face Design: Raised straight all ends Raised Face Height: 0.438 inches 1st end Raised Face Diameter:

NSN 4820-01-228-4260

Safety Relief Valve - Page 2 of 2



Media For Which Designe	Which Designe	ed
-------------------------	---------------	----

Liquid, ingested single response

Style Designator:

C1a angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0