

View Online at <https://aerobasegroup.com/nsn/4820-01-230-3493>

**Flange Diameter:**

6.125 inches

**Bonnet Type:**

Outside screw-yoke

**Bonnet Attachment Method:**

Bolted

**Bolt Hole Quantity:**

4

**Valve Operation Method:**

Manual

**Connection Type:**

Flange, round w/holes

**Features Provided:**

Bonnet packing

**Valve Size:**

1.500 inches

**Maximum Operating Pressure And Media For Which Designed:**

50.0 pounds per square inch steam and 740.0 pounds per square inch water-oil-gas

**Stem Type:**

Rising

**Maximum Operating Temperature And Media For Which Designed:**

1000.0 degrees fahrenheit steam and 100.0 degrees fahrenheit water-oil-gas

**Face To Face Distance:**

7.500 inches

**Flange Face Design:**

Raised

**Inlet Relationship With Outlet:**

Identical

**Pressure Class:**

300.0 pounds

**Special Features:**

Solid wedge; hard faced seats; conventional port; carbon steel trim

**Material:**

Steel uns k03504 body

**Material Specification:**

Astm a105 assn standard single material response body

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500a0