NSN 4820-01-230-5100

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-230-5100 **Thread Direction:** Right-hand all ends **Flow Control Device: Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 400.0 degrees fahrenheit single response **Connection Style:** Plain, optional end (pipe) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.750 inches all ends Material: Rubber polymethylene-perfluoroalkylene class fkm packing **Material Specification:** Qq-a-225/6 federal specification single material response body Media For Which Designed: Fuel/oil, hydrocarbon single response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response **Style Designator:** Straight thru **Thread Series Designator:** Npt all ends Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A530b0

NSN 4820-01-230-5100

Check Valve - Page 2 of 2



Mil-std (military Standard):

Mil-r-83248 spec.